## REDUCED 2.5MM PITCH: 9155-250

#### **General Information**





KYOCERA AVX Interconnect has extended its range of reduced battery board-to-board connectors. The new version, 9155-250, has a nominal working height of 4.5 mm, compared to the existing version, 9155-200, which has a nominal working height of 3 mm. These connectors are rated at 3 amps per contact on 2.5-millimeter centers. The 9155 series includes two through five position connectors that are end-to-end stackable.

The complete 9155 series of connectors from KYOCERA AVX offers the same advantages. Ultra-reliable, robust, gold-plated beryllium-copper contacts provide high-integrity connections in harsh environments with 5,000 mating operations and high-temperature nylon plastic for RoHS soldering. Additionally, the 9155-250 is made from halogen-free nylon.

#### **APPLICATIONS**

- · Handheld/portable devices requiring docking or cradle charging
- Patient monitoring or portable medical electronics
- Industrial devices requiring pluggable or programming modules
- Internet appliances requiring battery back-up
- Product Specification: Refer to 201-01-093

#### **FEATURES AND BENEFITS**

- · Insulator height 3.6mm
- Gold plated BeCu contacts provide high electrical and mechanical performance over 5000 mating cycles
- Halogen free high temperature nylon plastic, UL94V-0 rated
- End-to-end stackable

#### **ELECTRICAL**

- · Current Rating: 3 Amps / Contact
- Voltage Rating: 125 VAC (RMS) or DC equivalent


#### **ENVIRONMENTAL**


- · Operating Temperature: -40°C to +125°C
- Storage Temperature: -40°C to +70°C

#### **MECHANICAL**

- Insulator Material: High Temperature Halogen Free Plastic to UL94V-0 rated
- Contact Material: Beryllium Copper
- Plating: Gold on Nose, Pure Tin SMT terminations over

#### **HOW TO ORDER**











TDS-BTB-0027 | Rev 2

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

### **KYOCERA AVX:**

 $\frac{9155002251006}{009155003251006} \ \frac{9155003251006}{009155003251006} \ \frac{9155004251006}{009155003251006} \ \frac{009155004251006}{009155002251006}$